

Commercial Oil is for use in high traffic areas, where deep cleaning and oiling of the wood is required, in a single process. The oil is quick drying and therefore ideal for buildings such as airports, railway stations and public areas where it is not possible to seal off the area for an extended period of time. Commercial Oil cleans and maintains the wood thoroughly, leaving a surface that is both water repellent and maintained.

- **Cleaning and oiling in a single workflow**
- **Simple and quick-drying**
- **For high traffic areas**



Application area

For cleaning, oiling and care of previously oiled wood floors.

Work description

Preparation	It is important that the product, the room and the floor are at a temperature between 15°C and 30°C and that air humidity is approx. 50 %. Wood humidity must not exceed 12%. Make sure that the room is well-ventilated for optimal evaporation and drying time. If the surface is very dirty and stained, we recommend cleaning with WOCA Intensive Wood Cleaner, diluted 1:20 using a buffing machine and green polishing pad before the first application of Commercial Oil. Always remember to test on a less visible spot to check the compatibility of the surface with the product.
Treatment	Thoroughly shake the container of Commercial Oil, both before and during use. Apply the oil using a buffing machine and a green polishing pad. The oil should be polished well into the wood. The surface must not appear wet afterwards.
Note	Commercial Oil should be applied 2-4 times a year, or as required.

Drying time

Drying time	2 hours.
Drying time before washing	24 hours
Fully hard	24 hours.
Note	Do not expose the floor to water or clean it for the first 24 hours, while the oil is hardening. After 24 hours the floor can be cleaned with WOCA Commercial Soap, which gives the surface extra protection.



Technical data

Binder	Vegetable oil components
Density	0.80-0.85 g/ml
Solid content	Approx. 15-20%
Shelf life	3 years if unopened
Application Temperature	+15-30°C
Coverage	100 m ² /L, depending on wood type and surface
Coverage (diluted)	100 m ² /L, depending on wood type and surface
Colours	Natural
Cleaning of tools	WOCA Solvent or turpentine
Storage	+10-25°C. Keep out of reach of children. Must not be exposed to heat (e.g. sunlight). Store frost-free.
Hazard labelling	Due to the risk of self-ignition it is important that oil wetted cloths are soaked and disposed of in a tightly closed and water filled container after use.
VOC	Max: 660 g/l, Permitted value is 700 g/L (A/f (SB)):
Packaging	5 L

Maintenance and related products

Related products	Commercial Soap, #511056A
Accessories	Green polishing pad, 20mm, article no. 86158 Wool pad, article no. 88047

Contact

WOCA Denmark A/S
Tvæervej 6
DK - 6640 Lunderskov
T +45 9958 5600
info@wocadenmark.com
wocadenmark.com

This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pre-treatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.